

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/047172 A1

(51) International Patent Classification⁷: **H01L 23/58**

(21) International Application Number:
PCT/IB2003/005156

(22) International Filing Date:
13 November 2003 (13.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
102 54 325.9 21 November 2002 (21.11.2002) DE

(71) Applicant (for DE only): **PHILIPS INTELLECTUAL
PROPERTY & STANDARDS GMBH** [DE/DE]; Stein-
damm 94, 20099 Hamburg (DE).

(71) Applicant (for all designated States except DE, US):
KONINKLIJKE PHILIPS ELECTRONICS N.V.
[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven
(NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WAGNER, Mathias**
[DE/DE]; c/o Philips Intellectual Property & Standards

GmbH, Weissshausstr. 2, 52066 Aachen (DE). **GARBE,
Joachim** [DE/DE]; c/o Philips Intellectual Property &
Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).

(74) Agent: **MEYER, Michael**; Philips Intellectual Property &
Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: **ELECTRONIC MEMORY COMPONENT WITH PROTECTION AGAINST LIGHT ATTACK**



(57) **Abstract:** In order to further develop an electronic memory component (100 or 100'), comprising at least one memory cell matrix (10) which is embedded in and/or let into at least one doped receiving substrate (20), in such a way that a light incidence taking the form of a so-called light attack is detected directly or sensed immediately without dead times (= contribution to chip development), it is proposed, - that the receiving substrate (20) be covered and/or surrounded at least partially and/or on at least one of its surfaces remote from the memory cell matrix (10) by at least one top/protective substrate (30) oppositely doped to the receiving substrate (20) and - that at least one of the substrates (20 or 30), for example the receiving substrate (20) and/or in particular the top/protective substrate (30), be in contact (12a or 12b) or connection (32) with at least one circuit arrangement (24 or 34 respectively) for the detection of voltages or currents caused by charge carriers generated upon light incidence.